INSTALLATION INSTRUCTIONS LIQUID REPLACEMENT PEDALS

Congratulations on your purchase! Thank you for choosing Putco products! Please note: You must follow these instructions to install the parts correctly otherwise damage may occur. **Read all instructions before installation and check to see if all parts listed are included.**

KIT CONTENTS

Item#	Qty	Description
1	1	Brake pedal
2	1	Accelerator pedal
3	1	Parking Brake pedal
4	1	Bolt kit / w rench
5	1	11/64" drill bit

BOLT KIT CONTENTS

tem#	Qty	Description
1	12	Bolts
2	12	Nuts
3	1	Allen Wrench

RECOMMENDED TOOLS

Safety Tools 1.EyeProtection Special Tools 1.Power drill 2.Metal drill bit (11/64") Installation Tools

1.Wrench

FACTORY PEDAL REMOVAL & LIQUID PEDAL INSTALLATION



Pre-Installation Prep.

Verify the kit contents (check against parts listing). Remove the protective wrapping from the replacement pedals. Remove the factory installed rubber pedal covers by pulling at the pedal corners.



Insert bolts

Hold liquid solid billet pedals up to the factory pedal and install by inserting bolts and tightening the nut on the back.

Pedals

Your pedal kit may vary based on the vehicle and application purchased





LIMITED WARRANTY

Putco guarantees it's stainless steel and aluminum products against defects in workmanship and material for as long as you own your vehicle. All painted products have a 90 day warranty on the painted surface. Any defects resulting from faulty material or workmanship will be warranted by Putco and repaired or replaced at our discretion. Putco assumes no extra labor costs. Damages caused by freight carriers, improper installation, misuse, collision, or neglect will not be warranted by Putco. **Putco is not liable for any vehicle damage resulting from the installation of our Liquid Solid Billet Pedals.**



Mark bolt hole location and drill

Verify the kit contents (check against parts listing). Remove the protective wrapping from the replacement pedals. Remove the factory installed rubber pedal covers by pulling at the pedal corners.

